



FIXED HOOK USE			HEILA HLRM 140 6S				
M	6.28	8.35	10.42	12.48	14.6	16.82	19.03
KG	19,700	14,450	11,350	9,350	7,800	6,550	5,650
SINGLE LINE PULL USE							
M	5.80	7.86	9.94	12.00	14.12	16.34	18.54
KG	4000	4000	4000	4000	4000	4000	4000
DOUBLE LINE PULL USE							
M	5.96	8.02	10.09	12.16	14.28	16.50	18.70
KG	8000	8000	8000	8000	7800*	6550*	5650*

*LIMITED BY HYDRAULIC CAPACITY CRANE

Multi Purpose Multicat DESTINY

Summary

Shallow drafted multi-purpose hybrid multicat

Clear deck space	approx. 150 m ²
10 ton Bollard Pull	Duw 3000 m ³
Movable wheelhouse up to 10 mtr	
Stable work platform	
Ideally for port and coastal working as lifting, pushing, towing, diving, anchoring, pipelining and crewing	
Crew change up to 12 persons	
Optional tracks on the side	

Technical specifications & dimensions

Basic functions	General assistance
Classification	20 nM BV (MCA) 24/7
Flag	Dutch (NL) (option UK)

Dimensions

Length o.a.	23.50 mtr
Beam o.a.	11.45 mtr
Depth	min. 0.70 mtr
Height	4.00 - 10.00 mtr

Bunker Capacities

Gas Oil	cap. 23 m ³
Fresh water	cap. 25 m ³
Dirty Oil	cap. 1.5 m ³
Sewage	500 ltr

Performances

Speed approx. 10 knots

Engines/Propulsion

Propulsion	2x 2700 HD 6950 HD
Main Engines	Volvo Penta Tier 3 (stage V)
Total Output	Accupakket 300/600 kW 1000 BHP
General Generator sets	30 kVA S4S
Pushing capacity	ca. 3000 m ³

Deck Equipment

Towing/Anchor Winch	2x 50 tons
Deck Crane	1x 140 Tm. 6S 5600 kg at 19 m

Accommodation

Comfortable accommodation for 12 persons
All cabins are heated and air-conditioned 6x2 persons
All nautical equipment is available on board

Moon Pool (Surveying)

Breadth	550 mm
Length	760 mm

